

15" SLOW SCAN LCD PANEL MOUNT MONITOR

29LP151A71UN/1

HIGH QUALITY, SLOW SCAN LEGACY SYSTEM REPLACEMENTS

The 29LP151A571UN/3 Series of 15" LCD monitors has been designed primarily for Slow Scan Legacy Systems as replacements for CRT monitors. They utilize a modern XGA TFT panel and a KME-designed Analog-Digital interface board. All elements, including a toughened glass protection screen, have been packaged in a compact metal housing.

By special development of our own Signal Recognition and Scaling software, and access to an extensive library of older signal timings gained from 30+ years of CRT monitor manufacturing, KME has created a Multiscan ("Universal") flat panel monitor with unique 15kHz to 60kHz display capabilities. Some common Slow Scan Signal timings are factory pre-set. (see table below) New ones may be added on request. Other signals, which are close to those listed, will give a display but some adjustment may be necessary for full screen performance. The final settings can be easily stored for future use.

SOLUTIONS FOR SLOW SCAN MONITORS

- > **Specially designed for slow scan signals**
Accepts signal types CGA, EGA & all VESA standards up to SXGA. TTL, analog & interlaced signals accepted
- > **Deep dimming capability**
KME have developed a deep dimming solution for the slow scan range which provides smooth consistent dimming 100% to 0%.
- > **Inputs**
All monitors have BNC, 9-D & 15-D connectors
- > **Rugged metal construction with good stability**
The LCD monitor has been designed with solidity, being housed in a compact metal construction with a toughened glass protection screen.



H. kHz	V. Hz	Pixels		H. kHz	V. Hz	Pixels
15.625	50	714 * 288		15.63	50	560 * 275
15.63	60	808 * 238		15.72	60	564 * 240
15.72	60	508 * 240		15.72	60	604 * 240
15.72	60	640 * 200		16.10	50	564 * 304
16.276	70	640 * 220		16.79	70	577 * 215
17.85	50	508 * 338		21.83	60	640 * 350
20.65	50	640 * 384		24.78	60	640 * 384

15" SLOW SCAN LCD PANEL MOUNT MONITOR

29LP151A71UN/1

DATASHEET

Electrical Description		Mechanical Description	
TFT Characteristics:		Dimensions:	Weight: 6.5Kg
Type:	AM Colour TFT	Input:	15D BNC x5, 9D
Max Resolution:	1024 x 768 pixels	Housing	Painted aluminium
Active Display Area:	304 x 228 mm	User Controls:	Front Mounted
No. Colours:	16 million	On Screen buttons	Brightness, Contrast, H/V Position & Size, Frequency, Frequency Fine
Contrast Ratio:	450:1 typical		
Brightness:	250cd/m ² typical		
Viewing Angles (at CR>10):	130 o H, 110 o V		
Backlight Life:	50,000 hours typical		
Clock Rate:	112MHz max		
Sync. Type/Level:	Separate H&V (+/-ve) TTL or Composite (-ve) TTL or Sync-on-Green (-ve) 0.3V		
Signal Sync:	Analog RGB 0.7-1.0Vp-p or TTL RGB >2.75Vp-p		
Synchronisation Range:			
Horizontal scan:	15-60kHz		
Vertical scan:	40-100Hz		
Power Supply:	90-260V 50/60Hz Power Pack inside base		
Power Consumption:	35W Max	Part Numbers:	
Environmental:		Panel Model:	29LP151A71UN/1
Storage Temp:	-20 to 60°C		
Operating Temp:	0 to 50°C		
Due to a policy of continuous product development KME reserves the right to change specifications and descriptions without prior notification. All trademarks acknowledged.			

KENT MODULAR ELECTRONICS LTD
621 Maidstone Road
Rochester, Kent ME1 3QJ
T: +44 (0)1634 830123 F: +44 (0)1634 830619
E: sales@kme.co.uk W: www.kme.co.uk

